

NLS-FR4080

Desktop Barcode Scanner



Features

■ Quick to Switch Mode

The Switch at the top of the scanner allows users to swiftly toggle between the Normal mode and High Motion Tolerance mode.

■ Superior Motion Tolerance

Exceptional motion tolerance (2.5m/s) and large FOV (horizontal 51°, vertical 32°) enhance user experience.

■ IP52-rated Sealing

An IP52-rated seal protects the scanner against the ingress of dust, water and other contaminants

■ Snappy On-screen Barcode Capture

Armed with Newland's sixth-generation of **UIMG®** technology, this CPU-based scanner is capable of reading 1D as well as high-volume 2D barcodes on a screen covered with protective film.

■ 1.2m Drop Resistance

The scanner withstands multiple 1.2m drops to concrete (for six sides, one drop per side).

■ IR Trigger

The IR sensor in the scanner enables speedy capture of barcodes presented to it, markedly increasing throughput and productivity.

Application Scenarios

Cashier counters in department stores/supermarkets/convenience stores, ticket validation, customer service desks, O2O applications, etc.

Desktop Barcode Scanner

Performance	Image Sensor		1280×800 CMOS
	Illumination		White LED
	Symbologies	2D	PDF417, Data Matrix, QR Code, Micro QR Code, Aztec, etc.
		1D	EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN, Codabar, Code 128, Code 93, ITF-6, ITF-14, Interleaved 2 of 5, Industrial 25, Standard 25, Matrix 2 of 5, GS1 Databar, Code 39, Code 11, MSI-Plessey, Plessey, etc.
	Resolution*		≥3mil
	Typical Depth of Field*	EAN-13	10-210mm (13mil)
		QR Code	10-180mm (15mil)
	Motion Tolerance*		2.5m/s
	Scan Angle**		Pitch: ±50°, Roll: 360°, Skew: ±45°
	Field of View		Horizontal 51°, Vertical 32°
	Min. Symbol Contrast		25%
Mechanical/ Electrical	Interfaces		RS-232, USB
	Dimensions		83(W)×81(D)×148(H)mm
	Weight		293g
	Notification		Beep, LED indicator
	Rated Power Consumption		1041mW (typical)
	Operating Voltage		5VDC±5%
	Current@5VDC	Operating	219mA (typical)
Environmental	Operating Temperature		-20℃ to 60℃ (-4℉ to 140℉)
	Storage Temperature		-40℃ to 70℃ (-40℉ to 158℉)
	Humidity		5%~95% (non-condensing)
	ESD		±14 KV (air discharge); ±8 KV (direct discharge)
	Drop		1.2m drops to concrete (for six sides, one drop per side)
	Sealing		IP52
Certifications			FCC Part15 Class B, CE EMC Class B
Accessories	Cable	USB	Used to connect the scanner to a host device.
		RS-232	Used to connect the scanner to a host device.
	Power Adapter		DC5V power adapter to provide power for the scanner with RS-232 cable.

*Test conditions: T=23℃; Illumination=300lux using incandescent lamp; sample barcodes made by Newland.

**Test conditions: Scan Distance= (min. DOF + max. DOF)/2; T=23℃; Illumination=300lux using incandescent lamp;

2D: QR Code; 10 Bytes; Resolution=15mil; PCS=0.8.

Specifications are subject to change without notice.

Version: V1.1

Newland China

+86-591-83978605
contact@nlsan.com
www.newlandaidc.com

Newland Europe

+31(0)-345-87-0033
info@newland-id.com
www.newland-id.com

Newland North America

+1-510-490-3888
info@newlandna.com
www.newlandamerica.com

Newland Latin America

+1-239-598-0068
info@newlandla.com
www.newlandamerica.com

Newland Taiwan

+886-2-7731-5388
info@newland-id.com.tw
www.newland-id.com.tw

Newland Korea

+82-10-8990-4838
th.sung@newland-id.com.tw
www.newlandaidc.com