

VOYAGER EXTREME PERFORMANCE (XP) 1472g

Durable, Highly Accurate 2D Cordless Scanner

Designed for in-store retail environments requiring a highly accurate 2D scanning solution in a durable form factor, the Voyager™ Extreme Performance (XP) 1472g cordless scanner delivers industry-leading scanning capability on traditional barcodes and digital screens – even on damaged and difficult-to-read codes.

With better durability and more powerful scanning capabilities than previous models – or any competitive scanner in its class – the Voyager XP 1472g scanner is the perfect option for workflows that include 1D and 2D barcode reading and require a more robust and reliable solution. The Voyager XP 1472g scanner combines added durability and better scan capability at the same competitive price point as its predecessor. The scanner's extended scan distance will reach right to the bottom of the cart without bending and wasted time at the checkout.

Built on the platform of Honeywell's iconic Voyager series handheld scanners, the Voyager XP 1472g scanner is fully backward-compatible with existing Voyager accessories, reducing total cost of ownership.

Engineered to 30 drops at 1.8 m (6 ft) and 1,000 tumbles at 0.5 m (1.6 ft), the Voyager XP 1472g scanner is built to withstand busy point-of-sale scanning with much better accuracy than comparable solutions.



The Voyager XP 1472g cordless scanner combines enhanced reading of poor-quality and damaged codes with class-leading durability, reducing the risk of errors and operational slowdowns and avoiding the hidden cost of warranty.

FEATURES AND BENEFITS



Highly accurate and fast scanning of even damaged and poor-quality barcodes, with an extended scan distance to reach the bottom of the cart without bending and wasted time at point of sale.



Enhanced performance on the codes stores scan every day, including digital coupons, codes, and wallets on customers' smartphones, as well as merchandise codes at the register.



Honeywell Operational Intelligence software delivers on-demand scan insights, enabling higher employee productivity and throughput.



A longer Bluetooth range compared to competitive devices enables greater operational flexibility for line busting or peak season satellite POS stations.

Honeywell

Voyager Extreme Performance (XP) 1472g Technical Specifications

WIRELESS

Radio/Range: 2.4 GHz to 2.5 GHz (ISM Band)
Adaptive Frequency Hopping
Bluetooth v4.2
30 m (98 ft) line of sight with Honeywell charger/communication base
Power Options:

Battery: 2400 mAh Li-ion minimum
Number of Scans: Up to 50,000 scans per charge
Expected Duration of Operation: 14 hours
Expected Charge Time: 4.5 hours
User Indicators: Good Decode LEDs, Rear View LEDs, Beeper (adjustable tone and volume)

MECHANICAL/ELECTRICAL

Dimensions (L x W x H): 62 mm x 173 mm x 82 mm (2.5 in x 6.8 in x 3.2 in)
Charger/Communication Base: (CCB01-010BT-V1N) 132 mm x 102 mm x 81 mm (5.2 in x 4.0 in x 3.2 in)
Scanner Weight: 210 g (7.4 oz)
Charger/Communication Base: 179 g (6.3 oz)
Operating Power (Charging): Charger/Communication Base: 179 g (6.3 oz)
Standby Power: Charger/Communication Base: 0.5 W (0.1A @ 5V)
Host System Interfaces: USB, Keyboard Wedge, RS-232, RS485 support for IBM 46xx (RS485)

ENVIRONMENTAL

Operating Temperature:
Scanner:
Charging: 5°C to 40°C (41°F to 104°F)
Non-Charging: 0°C to 50°C (23°F to 122°F)
Charger/Communication Base:
Charging: 5°C to 40°C (41°F to 104°F)
Non-Charging: 0°C to 50°C (32°F to 122°F)

Storage Temperature:
Scanner:
For storage up to 90 days: -20°C to 35°C (-4°F to 95°F)
For storage up to 1 year: -20°C to 20°C (-4°F to 68°F)
Charger/Communication Base: -40°C to 70°C (-40°F to 158°F)
Electrostatic Discharge (ESD) (Scanners and Cradles): ±8 kV indirect coupling plane, ±15 kV direct air
Humidity: 0% to 95% relative humidity, non-condensing
Tumble Spec: 1,000 0.5 m (1.6 ft) tumbles (impacts)
Drop: Engineered to withstand 30 1.8 m (6 ft) drops to concrete
Environmental Sealing: IP42
Light Levels: 0 to 100,000 lux (9,290 foot-candles)

SCAN PERFORMANCE

Scan Pattern: Area Image (1040 x 720 pixel array)
Motion Tolerance: 70 cm/s (27.6 in/s) for 13 mil UPC at optimal focus
Scan Angle:
Horizontal: 39.2° nominal
Vertical: 27.4° nominal
Roll, Pitch, Skew: ±180°, ±65°, ±70°
Barcode Types: Reads standard 1D, PDF, 2D, and DotCode symbologies
Note: Decode capabilities dependent on configuration.
Warranty: 3-year factory warranty

DECODE RANGES (DoF)

TYPICAL PERFORMANCE*	STANDARD RANGE (SR)
5 mil Code 39	20 mm – 205 mm (0.8 in – 8.1 in)
13 mil UPC	18 mm – 400 mm (0.7 in – 15.8 in)
6.7 mil PDF417	15 mm – 185 mm (0.6 in – 7.3 in)
10 mil DM**	10 mm – 165 mm (0.4 in – 6.5 in)
20 mil QR	5 mm – 325 mm (0.2 in – 12.8 in)

* Performance may be impacted by barcode quality and environmental conditions.
** Data Matrix (DM)

For a complete listing of all compliance approvals and certifications, please visit www.honeywellaidc.com/compliance.
For a complete listing of all supported barcode symbologies, please visit www.honeywellaidc.com/symbologies.
Voyager is a trademark or registered trademark of Honeywell International Inc.
Bluetooth is a trademark or registered trademark of Bluetooth SG, Inc.
All other trademarks are the property of their respective owners.

For more information
www.honeywellaidc.com

Honeywell Safety and Productivity Solutions
9680 Old Bales Road
Fort Mill, SC 29707
800-582-4263
www.honeywell.com